

Unser allgemeines Lagermattenprogramm

Typ	Aufbau		längs quer Durchm.	Rand längs Durchm. / Anzahl links - rechts	Länge Breite [mm]	Überstände		Gewicht je Matte   pro m <sup>2</sup> [kg]
	Abstand	°				oben links	unten rechts	
Q188A	150	°	6,0		5000	100	100	32,4   3,01
	150	°	6,0		2150	25	25	
Q257A	150	°	7,0		5000	100	100	44,1   4,10
	150	°	7,0		2150	25	25	
Q355A	150	°	8,0		5000	100	100	57,7   5,37
	150	°	8,0		2150	25	25	
Q377A	150	°	6,0 d	6,0 / 4 - 4	6000	100	100	67,6   5,24
	100	°	7,0		2150	25	25	
Q513A	150	°	7,0 d	7,0 / 4 - 4	6000	100	100	90,0   6,98
	100	°	8,0		2150	25	25	
R188A	150	°	6,0		5000	125	125	26,2   2,44
	250	°	6,0		2150	25	25	
R257A	150	°	7,0		5000	125	125	32,2   3,00
	250	°	6,0		2150	25	25	
R355A	150	°	8,0		5000	125	125	39,2   3,65
	250	°	6,0		2150	25	25	
R377A	150	°	6,0 d	6,0 / 2 - 2	6000	125	125	46,1   3,57
	250	°	6,0		2150	25	25	
R513A	150	°	7,0 d	7,0 / 2 - 2	6000	125	125	58,6   4,54
	250	°	6,0		2150	25	25	

Ihr Ansprechpartner für Betonstahlmatten in der REMAG Niederlassung Südbayern ist

**Herr Römer**

Tel.:089-90 99 75-153

Fax.089-90 99 75-159

alexander.roemer@remag.de