

Neues Lagermattenprogramm ab 01.01.2008

Mattentyp	Länge / Breite [m]	Gewicht je Matte je m ² [kg]	Mattenaufbau in Längsrichtung und Querrichtung				Überstände Anfang Ende links rechts [mm]	
			Stababstände [mm]	Stabdurchmesser Innenbereich Randbereich [mm]		Anzahl der Längsrandstäbe links rechts		
Q188A	6,00 / 2,30	41,7 3,02	150	°	6,0		75	
			150	°	6,0		25	
Q257A		56,8 4,12	150	150	°	7,0		75
				150	°	7,0		25
Q335A		74,3 5,38	150	150	°	8,0		75
				150	°	8,0		25
Q424A	84,4 6,12	150	150	°	9,0	/ 7,0	- 4 / 4	75
			150	°	9,0		25	
Q524A	100,9 7,31	150	150	°	10,0	/ 7,0	- 4 / 4	75
			150	°	10,0		25	
Q636A	6,00 / 2,35	132,0 9,36	100	°	9,0	/ 7,0	- 4 / 4	62,5
			125	°	10,0		25	
R188A	6,00 / 2,30	33,6 2,43	150	°	6,0		125	
			250	°	6,0		25	
R257A		41,2 2,99	150	150	°	7,0		125
				250	°	6,0		25
R335A		50,2 3,64	150	150	°	8,0		125
				250	°	6,0		25
R424A	67,2 4,87	150	150	°	9,0	/ 8,0	- 2 / 2	125
			250	°	8,0		25	
R524A	75,7 5,49	150	150	°	10,0	/ 8,0	- 2 / 2	125
			250	°	8,0		25	